

GAA-001

AUDIO AMPLIFIER

Mini Auto Covert Pick-Up Mic



Key Features

- Covert style
- Up to 80 sq.m monitoring range
- -30dB sensitivity
- Overload protection
- Power in / Power passthrough connection

The Genie **GAA-001** is a covert microphone with a built-in preamp. It can be used in conjunction with various Genie DVR's and cameras.



Specification

Monitoring Range	10 ~ 80 (sq.m)
Transmitting Distance (Shielded Cable)	Up to 2km
Frequency Response	20Hz ~ 20kHz
Sensitivity	-30dB
SNR	70dB (1m / 40dB) 40dB (10m / 40dB), 1KHz at 1 Pa
Polar Pattern	Omni-Directional
Dynamic Range	104dB (1 KHz at Max dB SPL)
Maximum Level Input	120dB SPL (1 KHz, THD 1%)
Impedance	600ohm (imbalance)
Signal Output Extent	2.5Vpp/-25db
Microphone	Electret condenser
Special Circuit	DSP de-noise, AGC circuit
Protect Circuit	Over-load protection
Audio Preamp	Built-in
Output Connector	Power, Audio and Public GND
Voltage	DC12V (9~12V)
Current	20 mA
Temperature	-25°C ~ 70°C
Material	PVC
Dimensions	3 × 0.5 mm

Accessories



GAIPLEAD
IP Audio Lead