

WTX-2BH-26

KEY FOBBS & CARDS

2 Button 26 Bit Wiegand Transmitter with HID 125KHz Prox 433MHz



Key Features

- MAXSecure™ – Unique security feature
- Contactless (Button press : Up to 60m, Proximity Presentation Distance : Up to 88mm)
- Built in eyelet – can be easily attached to a keyring
- Wiegand output interface
- ETL listed – Independently tested and certified to conform to UL Standard 294
- Rated to typically provide more than 250,000 button presses under normal conditions
- Electronics sealed in a weather resistant enclosure (IP65)

The Genie **WTX-2BH-26** is a long range 2 button Wiegand transmitter powered by the most reliable and common battery as well as being equipped with a potted proximity contactless smart card module.



Specification

Frequency	Button Press : 433MHz, Presentation : 125KHz
Marking	Date code and ID
Button Press Transmission	Rolling code and encryption
Battery	Single replaceable CR2032, 3.3V, lithium battery
Compatibility	Button Press : WRR-2 Receiver, Presentation : Pyramid readers and others
Read Range	Button Press : Up to 60m, Proximity Presentation Distance: Up to 88mm
Interface	Wiegand (26-bit industry standard and custom Wiegand formats)
LED	Integrated red LED standard (activated upon button press)
IP Rating	IP65
Operating Temperature	-40°C to +50°C, 5-95% RH (Non-condensing)
Dimensions	37 × 63.5 × 14.2 mm
Weight	20g