KEY FOBS & CARDS

2 Button 13.56MHz Wiegand Long Range Transmitter



Key Features

- MAXSecure™ Unique security feature
- Contactless (Button press : Up to 60m, Proximity Presentation Distance : Up to 88mm)
- Built in eyelet can be easily attached to a keyring
- Wiegand output interface
- ETL listed Independently tested and certified to conform to UL Standard 294
- Rated to typically provide more than 250,000 button presses under normal conditions
- Electronics sealed in a weather resistant enclosure (IP65)

The Genie WTX-2BM is a long range 2 button Wiegand transmitter powered by the most reliable and common battery as well as being equipped with a potted proximity contactless smart card module.





Specification

Frequency	Button Press : 433MHz,
	Presentation : 13.56MHz
Marking	Date code and ID
Button Press Transmission	Rolling code and encryption
Battery	Single replaceable CR2032, 3.3V, lithium battery
Compatibility	Button Press : WRR-2 Receiver, Presentation : Pyramid readers and others
Read Range	Button Press : Up to 60m, Proximity Presentation Distance : Up to 88mm
Interface	Wiegand (26-bit industry standard and custom Wiegand formats)
LED	Integrated red LED standard (activated upon button press)
IP Rating	IP65
Operating Temperature	-40°C to +50°C, 5–95% RH (Non-condensing)
Dimensions	37 × 63.5 × 14.2 mm
Weight	20g

