NETWORK VIDEO RECORDER

16 Channel H.265 Optimised NVR with 2HDD Bays



Key Features

- Supports 16 channel 5MP, 4MP, 3MP, 1080p, 960p and 720p IP input
- Adopt standard H.265 and H.264 high profile compression format to get high quality video at much lower bit rate
- Intuitive and user friendly Graphic User Interface (GUI), Windows style operation by mouse
- Multi-mode recording: Manual / Timer / Motion / Sensor
- Search: Time slice, time, event (Manual, sensor, motion), Tag search

- Express and flexible backup via USB, network etc.
- Pentaplex : Preview, Record, Playback, Backup and Remote Access
- DHCP, DDNS, PPPoE network protocol and CMS supported
- Remote control via IE or CMS: Preview, playback, backup, PTZ and configuration
- 1080p HD output, true high resolution display
- 16 channel simultaneous playback
- Authorisation management, log view and device status view

- Multi-user online simultaneously
- 16 PoE network ports supported by IPC direct connection to NVR, supports PoE power supply
- Support PTZ preset and auto cruise, up to 255 presets and 8 cruises
- Support NAT function and QR code scanning by mobile phone and iPad
- Powerful smart phone & iPad surveillance with iOS and Android OS

The Genie 'Optimised' WONVR216P5 network video recorder is a 16 channel PoE NVR with resolution on every channel of up to 5MP. There are 16 PoE ports available, 2 bays for hard drives and this versatile NVR fully supports up to 16 channels of simultaneous playback.





Specification

System

OS Embedded Linux

Video

Network Input	16 CH IPC input
Network Access Format	5MP / 4MP / 3MP / 1080p / 960p / 720p @ 25 / 30fps
Output	HDMI x 1 : 1920×1080 / 1280×1024 / 1024×768 VGA x 1 : 1920×1080 / 1280×1024 / 1024×768
Compression	Standard H.265, H.264
Incoming Bandwidth	112Mbps
Outgoing Bandwidth	112Mbps

Audio

	16 channel IPC audio input
Two Way Audio	RCA x 1
Audio Local Output	RCA x 1

Record

Record Stream	Dual stream recording
Resolution	5MP / 4MP / 3MP / 1080p / 960p / 720p @ 25 / 30fps
Mode	Manual, Timer, Motion, Sensor

Mobile Device

OS	iOS, Android
	.

Storage

HDD	SATA x 2, up to 8TB per HDD
-----	-----------------------------

Playback

Simultaneous Playback	16 channel max.
Search	Time slice / Time / Event / Tag search
Smart Search	Highlight colours to display the camera record in a certain period of time, different colours refer to different record events
Function	Play, Pause, FF, FB, Digital zoom, etc

Network

Interface	RJ45 10 / 100 / 1000 Mbps x 1
Protocol	TCP / IP, PPPOE, DHCP, DNS, DDNS, UPnP, NTP, SMTP
PoF Port	DI/ ₁ 5 v 14

Record

Stream	Dual stream recording
Resolution	5MP / 4MP / 3MP / 1080p / 960p / 720p @ 25 / 30fps
Mode	Manual, Timer, Motion, Sensor

Alarm

Mode	Manual, Sensor, Motion, Exception
Input	Support IPC alarm input
Output	Support IPC alarm output
Triagering	Record. Snap. Preset. E-mail. etc.

Remote Monitoring

Immix	Compatible with Immix via RTSP only
	(2-way audio not supported)
Sentinel	Yes, Firmware 1.1.0 or later

Backup

Local Backup	USB Stick, USB mobile HDD
Network Backup	Yes

Port

USB	USB 2.0 × 2
Remote Controller	Optional

Others

Power Supply	DC48V
Consumption	<15W (Without HDD)
Working Environment	Temperature: -10°C – 50°C, Humidity: 10% – 90%
Dimensions	380 × 268 × 52 mm



Dimensions





