

LMV-42M

# MONITOR

42" HDMI and VGA LED Monitor



## Key Features

- 1920 × 1080
- 9ms fast response time
- HDMI inputs
- 16:9 aspect ratio
- Supports 24/7 continuous use
- Desk stand (Detachable)
- Standard and VESA mount options

The Genie LMV-42M is a 42" LED monitor. The monitor has a fast response time of 9ms so no image ghosting and is also able to continually work for 24/7. The monitor features a detachable stand and is able to fit standard and VESA mount options.



## Specification

### Monitor

<b>Panel Type</b>	LED
<b>Maximum Resolution</b>	1920 (H) x 1080 (V)
<b>Active Display Area</b>	919.296 (H) x 517.104 (V)
<b>Pixel Pitch</b>	0.0798 (V) x 0.2394 (V)mm
<b>Bezel Thickness</b>	Left / Right / Top / Bottom 22mm
<b>Contrast Ratio</b>	5000:1
<b>Brightness</b>	350cd/m2
<b>Response Time</b>	9ms
<b>Viewing Angle</b>	178°/178° (H/V)
<b>Display Colours</b>	16.7M
<b>Video Synchronisation</b>	Yes
<b>PC Compatibility</b>	30-60KHz (H) / 56-75KHz (V)
<b>Adjustable Colour Temperature</b>	9300K / 6500K / 5800K / User
<b>Video Compatibility</b>	NTSC/PAL
<b>Aspect Ratio</b>	16:9
<b>VGA Auto Frequency Correction</b>	Yes
<b>Number of Speakers</b>	2 (2 x 5W)
<b>Sound Demodulation</b>	Audio, Stereo
<b>Mute</b>	Yes
<b>Volume +/- Power On/Off</b>	Yes

### Interface

<b>Video Interface</b>	1x BNC Composite In, 1x BNC Composite Out, 1xVGA, 1xHDMI
<b>Audio Interface</b>	1x PC Audio
<b>Power Interface</b>	DC In x 1
<b>Termination</b>	75 Ohm

### Others

<b>OSD Controls</b>	Contrast, Brightness, Colour, Sharpness, Colour Temperature
<b>OSD Languages</b>	English, German, Italian, Spanish, French, Russian, Portuguese and Polish
<b>Work Humidity</b>	5% - 80%
<b>Work Temperature</b>	0°/+50°
<b>Power Supply</b>	Built-in
<b>Power Consumption</b>	<80W
<b>Voltage</b>	AC110V - 240V 50/60 Hz
<b>Vesa Standard Mount</b>	200 x 200mm, 200 x 400mm
<b>Stand Type</b>	Desktop
<b>Colour</b>	Black
<b>Button Position</b>	Rear Face, Right Bottom
<b>Case Type</b>	Metal
<b>Dimensions</b>	965.8 x 563.6 x 59.56 mm
<b>Net Weight</b>	16.8 Kg

# Dimensions

