HDUBKIT2

4K PASSIVE BALUN

AHD, CVI, TVI and CVBS Passive Video Balun Kit - 2x Transceivers



Key Features

- 1 channel HD analogue video signal Over CAT5e/6 Cable
- Passive, no need for a power supply
- Plug-and-play, real-time and stable
- AHD, HD-CVI, HD-TVI, CVBS 4-in-1 compatible design
- 500m matches the passive transceiver, 650m matches active transceiver
- Excellent anti-inteference, surge protection and ESD protection

The Genie HDUBKIT2 is a single channel HD analogue video passive UTP balun. It transfers 1 channel of video at up to 4K (8 megapixel) resolution over a CAT5e/6 UTP cable.



genie

Transmission Distance

Recommend Transmission Distance (with passive product) HDCVI – 720p: 400m, 1080p: 250m 4MP: 250m, 8MP: 200m HDTVI – 720p: 250m, 1080p: 250m 4MP: 200m, 8MP: 160m AHD – 720p: 300m, 1080p: 300m, 4MP: 270m, 8MP: 250m Analogue Video – 500m

Protection

Surge Protection	2KV Per: IEC61000-4-5
ESD	Level 3,1a Contact Discharge, Level 3,1b Air Discharge


Others

Outer Shell	ABS
Operation Temperature	10°C-55°C
Storage Temperature	-40°C-85°C
Relative Humidity	0%-95% (Non-condensing)
Net Weight	20g

Video Properties

Coaxial Video Connector	Male BNC Port
Twisted-Pair Video Port	Push-Click Terminal
Video Compatibility Bandwidth	HDCVI/HDTVI/AHD/Analogue, PAL/NTSC/SECAM Video 0~75MHz

Application



Sales +44(0)1707 330541 Enquiries sales@genieproducts.co.uk Website www.genieproducts.co.uk