

CADIP4NEBVAF

# EYEBALL CAMERA

4MP Active Deterrent Eyeball Camera with 2.8–12mm Lens



## Key Features

- Maximum resolution: 2592 × 1520
- 30 ~ 40m IR or white light range
- H.265+/H265/H.264+/H264/ MJPEG coding
- 3D DNR, true WDR, HLC, BLC, Defog and ROI coding
- Built-in micro SD card slot, up to 256GB
- DC12V/PoE power supply
- Supports three streams
- Intelligent analytics
- Support remote monitoring by smart phones and tablet PC's with iOS and Android OS
- IP66 ingress protection
- Supports image distortion correction

The Genie CADIP4NEBVAF is a 4MP IP IR active deterrent eyeball camera with a 2.8-12mm auto focus lens. The camera features dual illumination and intelligent analytics.



genie

# Specification

## Camera

<b>Image Sensor</b>	1 / 3" CMOS
<b>Image Size</b>	2592 × 1520
<b>Electronic Shutter</b>	1 / 3s ~ 1 / 100000s
<b>Iris Type</b>	DC Iris
<b>Minimum Illumination</b>	0.02 Lux @ F1.4, AGC ON, 0 Lux with LED
<b>Lens</b>	2.8-12mm @ F1.4
<b>Field of View</b>	Horizontal: 96° ~32.33°; Vertical: 53.67°~19.63°; Diagonal: 114.17° ~36.33°
<b>Focus</b>	Motorised
<b>Lens Mount</b>	Ø14
<b>Wide Dynamic Range</b>	120dB
<b>BLC</b>	Yes
<b>HLC</b>	Yes
<b>Defog</b>	Yes
<b>Digital NR</b>	2D / 3D DNR
<b>S/N Ratio</b>	≥50dB
<b>Angle Adjustment</b>	Pan: 0°~360°, Tilt: 0°~75°, Rotation: 0°~360°

## Image

<b>Video Compression</b>	Main stream: H.265+ / H.265 / H.264+ / H.264 Sub/Third stream: H.265+ / H.265 / H.264+ / H.264 / MJPEG
<b>H.264 Compression Standard</b>	Baseline Profile, Main Profile, High Profile
<b>Resolution</b>	4MP (2592 × 1520), 2K (2560 × 1440), 3MP (2304 × 1296), 1080P (1920 × 1080), 720P (1280 × 720), D1, VGA (640 × 480), CIF, 480 × 240
<b>Main Stream</b>	4MP, 2K, 3MP, 1080p (60Hz : 1 ~ 30fps, 50Hz: 1~25fps) HFR mode: 1080p, 720p (60Hz : 1 ~ 60fps, 50Hz: 1~50fps)
<b>Sub Stream</b>	720p, D1, VGA, CIF (60Hz : 1 ~ 30fps, 50Hz: 1~25fps)
<b>Third Stream</b>	D1, VGA, CIF, 480 × 240 (60Hz : 1 ~ 30fps, 50Hz: 1~25fps)
<b>Bit Rate</b>	64 Kbps ~ 8 Mbps
<b>Bit Rate Type</b>	VBR / CBR
<b>Audio Compression</b>	G711A / U
<b>Image Settings</b>	ROI, Saturation, Brightness, Hue, Contrast, Wide Dynamic, Sharpen, Image Flip, Image Mirror, NR, etc. Adjustable through client software or web browser.
<b>ROI</b>	Each ROI to be configured separately

## Functions

<b>Remote Monitoring</b>	Web client, NVR, NVMS2.0, mobile app
<b>Web Browser</b>	IE11 (plug-in required), Chrome 89.0+, Edge 89.0+, Firefox 87.0+, Safari 14.0+
<b>Online Connection</b>	Supports simultaneous monitoring for up to 10 users. Supports multi-stream real time transmission.
<b>Network Protocol</b>	UDP, IPv4, IPv6, DHCP, NTP, RTSP, RTP, RTCP, PPPoE, DDNS, SMTP, FTP, SNMP, RTMP, HTTP, 802.1x, UPnP, HTTPs, QoS
<b>Interface Protocol</b>	Onvif compatible
<b>Intelligent Analytics</b>	Line crossing detection (human / vehicle classification), region entrance / exiting / intrusion (human / vehicle classification) Sound, Light & Flashing Red/Blue LED alerts Scene change, video blur and video colour cast detection Face detection and face capture Abandoned/missing object detection, heat map, target counting, crowd density detection
<b>Storage</b>	Network remote storage, micro SD card storage
<b>Smart Alarm</b>	Motion detection, sensor alarm, SD card error, SD card full, IP address conflict, cable connection
<b>General Function</b>	Watermark, IP address filtering, video mask, heartbeat, password protection, image distortion correction
<b>Security</b>	Video encryption, firmware encryption, HTTPs encryption, configuration encryption, illegal login lock, IP address filtering, 802.1x authentication, basic and digest authentication for HTTP/HTTPs
<b>PoE</b>	Yes , IEEE802.3af
<b>IR Distance</b>	30 ~ 40 m White light range: 30 ~ 40 m


## Interface

<b>Network</b>	RJ45 10M/100M self-adaptive ethernet port
<b>Video Output</b>	No
<b>Audio</b>	1CH audio input, 1CH audio output, 1CH built-in speaker, 1CH built-in microphone
<b>Alarm</b>	1CH alarm input, 1CH alarm output
<b>Storage</b>	Built-in micro SD card slot, up to 256GB
<b>Hardware Reset</b>	Yes


## Others

<b>Ingress Protection</b>	IP66
<b>Power Supply</b>	DC12V / PoE
<b>Power Consumption</b>	< 12W
<b>Operating Environment</b>	- 30 °C ~ 60°C (-22°F~140°F) Humidity: Less than 95% (Non-condensing)
<b>Dimensions</b>	Ø111.5 × 99.6 mm
<b>Weight</b>	Approx. 0.64 Kg

## Dimensions



## Accessories



**WJBBVWP**  
Water Resistant Junction  
Box - White



**WJBEBV**  
Junction Box for Varifocal  
and Auto Focus Eyeball  
Cameras - White




**WIPSWM**  
Surface Mount Wall  
Bracket (Junction Box NOT  
included) - White



**WBEBVW**  
Wall Bracket for Eyeball  
Cameras - White



**WIPMPM**  
Multi Purpose Pole Mount  
Bracket - White



**WIPPCM**  
Multi Purpose Corner  
Mount Bracket - White