

GHDJBIR

# COVERT CAMERA

2MP IR Junction Box Camera



## Key Features

- 1/ 2.8" CMOS image sensor
- Full HD Mega Pixel (1080P)
- 4 in 1 (AHD, CVI, TVI, CVBS)
- 5-10m Invisible IR
- 4.3mm conical pinhole lens with ICR
- 3D DNR (Digital Noise Reduction)
- Sens-up
- D-WDR (Digital Wide Dynamic Range)
- UTC (OSD via coaxial cable)
- IP-66
- DC12V

The Genie GHDJBIR is a 2MP 1080p conical pinhole camera housed in a wall mount junction box. The unit is suitable for discreet and covert operations.



## Specification

### Camera

<b>Image Sensor</b>	Sony STARVIS 1/2.8" 5.69 CMOS Image Sensor
<b>Scan Method</b>	Progressive Scan
<b>Active Pixel</b>	1920(H) x 1080(V)
<b>Day &amp; Night</b>	Auto / Colour / B&W / External
<b>Privacy Zone</b>	4 Masks
<b>Motion Detection</b>	Off/On
<b>DNR</b>	Off / Low / Middle / High
<b>D-WDR</b>	Off/0 ~ 8
<b>Defog</b>	Off / Auto
<b>Shutter Speed</b>	(1/50(60) ~ 1/50,000 sec)
<b>Colour Adjust</b>	Bright / Sharpness / Backlight
<b>White Balance</b>	Auto (Indoor) / Auto (Outdoor)
<b>Image Mirror</b>	Off / Mirror / Flip(V) / Rotate
<b>Power Supply</b>	DC12V ±10%
<b>Lens</b>	4.3mm conical pinhole (ICR)
<b>IR</b>	940nm
<b>Joystick</b>	Yes

### Video

<b>Resolution and Frame Rate</b>	1080p@30fps/1080p@25fps
<b>Video Output</b>	Universal AHD, CVI, TVI : 1080P, Analog: NTSC/ PAL CVBS

### Others

<b>Operating Temperature</b>	0°C ~ +50°C
<b>S/N Ratio</b>	More than 50dB (AGC off)
<b>AGC</b>	Off/0 - 15
<b>Language</b>	English/Chinese/Germany/French/ Italian/ Spanish/Polish/Russian/ Portuguese/ Dutch/Turkish/Korean/ Japanese
<b>Power Source</b>	DC12V ±10%
<b>Power Consumption</b>	Max 4.0 Watt at IR on
<b>SENS- UP</b>	Off/X2 - X30
<b>Operating Temperature</b>	-20°C to 60°C
<b>Operating Humidity</b>	10% to 85%
<b>Dimensions</b>	80(W)x 150(L) x 72(H)
<b>Weight</b>	Approx 330g