

WAHDN5162A

# DIGITAL VIDEO RECORDER

16 Channel 5-in-1 High Definition 1080p DVR with 1HDD Bay and Alarms



## Key Features

- Supports 16 CH TVI / AHD / CVI 5MP / 4MP / 1080P / 720P / WD1 video input
- Supports 8 CH 5MP / 4MP / 3MP / 1080P / 960P / 720P IP video input
- 8CH analog video input can be switched to 8CH IP video input
- Standard H.265 high profile compression format to get high-quality video at much lower bit rate
- Intuitive and user-friendly Graphics User Interface (GUI), window style operation by mouse
- Multi-mode recording: manual / timed / motion / sensor / AI recording
- Playback : 16 CH simultaneous playback
- Search: time slice, time, event, tag and smart search
- Express and flexible backup via USB, network and so on
- Pentaplex: preview, record, playback, backup and remote access
- DHCP, DDNS, PPPoE network protocol
- Remote control via Web Client or CMS : preview, playback, backup, PTZ and configuration
- Support remote network transmission and remote surveillance with mobile device
- Authorization management, log review and device status review
- 1080P output, true high resolution display
- Supports PTZ preset and auto cruise, up to 255 presets and 8 cruises
- Supports NAT function and QRCode scanning by mobile phones
- Powerful mobile surveillance by smart phones with iOS and Andriod OS

The Genie **WAHDN5162A** is a 5-in-1 DVR compatible with AHD, TVI, CVI, CVBS and IP cameras available in 4 and 8 channel formats. The DVR has the ability to connect to analogue and IP cameras simultaneously and encode the video streams using the H.265 high profile compression format which gives longer recording times compared to H.264 encoding. Real time recording is achievable up to 1080p video supporting resolution up to 5MP in AHD, TVI and IP. The **WAHDN5162A** is a highly versatile cost effective solution suitable for many CCTV applications.



genie

# Specification

## System

**OS** Embedded Linux

## Video

<b>Analogue Video Input</b>	BNC x16 BNC interface (1.0Vp-p; 75Ω) TVI / AHD / CVI : 5MP @ 20fps; 4MP / 1080P / 720P / WD1 @ 30fps (live)
<b>IP Video Input</b>	8CH (up to 16CH) Up to 5MP @ 30fps
<b>Total Input</b>	24CH
<b>Output</b>	HDMI × 1 : 1920×1080 / 1280×1024 / 1024×768  VGA × 1 : 1920 × 1080 / 1280 × 1024 / 1024 × 768  BNC × 1 : CVBS (used as the main or spot output)
<b>Compression</b>	H.264 / H.265 / H.265+
<b>Multi-screen Display</b>	1 / 4 / 6 / 8 / 9 / 13 / 16 / 25

## Audio

<b>Input</b>	RCA x 8
<b>Output</b>	RCA x 1 (Linear, 600Ω)
<b>Two-Way Audio</b>	Take up channel one audio input
<b>Compression</b>	G.711 (U/A)

## Record

<b>Resolution</b>	5MP Lite / 4MP Lite / 1080P/1080P Lite / 720P / WD1 Analog Channel: 5MP Lite@10fps (PAL / NTSC); 4MP Lite/1080P@12fps(PAL) / 15fps (NTSC); 1080P Lite/720P/WD1/D1@25fps (PAL) / 30fps (NTSC)
<b>Frame Rate</b>	IP Channel: 25fps (PAL) / 30fps (NTSC)
<b>Bit Rate</b>	32Kbps ~ 5Mbps
<b>Mode</b>	Manual, Timer, Motion, Smart Event

## Playback

<b>Playback</b>	16CH
<b>Search</b>	Time Slice / Time / Event / Tag Search
<b>Smart Search</b>	Highlight colours to display the camera record in a certain period of time, different colours refer to different record events
<b>Function</b>	Play, Pause, FF, FB, Digital Zoom, etc.

## Alarm

<b>Mode</b>	Manual, Motion, Exception, Smart Event
<b>Input</b>	16CH
<b>Output</b>	4CH

## AI Function

<b>Smart Motion Detection Performance</b>	16CH
<b>Perimeter Protection Performance</b>	1CH

## Network

<b>Interface</b>	RJ 45 1000Mbps × 1
<b>Protocol</b>	TCP / IP, PPPoE, DHCP, DNS, DDNS, UPnP, HTTP, HTTPS, NTP, SMTP
<b>Incoming Bandwidth</b>	32Mbps (max. 64Mbps)
<b>Outgoing Bandwidth</b>	96Mbps
<b>Client Connection</b>	Max. 10 users access

## Mobile Device

**OS** iOS, Android

## Storage

**HDD** SATA×2, up to 10TB per HDD; E-SATA×1

## Backup

<b>Local Backup</b>	U disk, USB mobile HDD
<b>Network Backup</b>	Yes

## Port

<b>RS485</b>	Yes (Half-duplex), Connect to PTZ or Keyboard
<b>USB</b>	USB 2.0 ×1; USB3.0×1
<b>Remote Controller</b>	Optional

## Others

---

<b>Power Supply</b>	DC12V / 4A
<b>Consumption</b>	≤ 15W ( without HDD )
<b>Dimensions(mm)</b>	380 × 268 × 45 ( W × D × H )
<b>Working Environment</b>	-10~50°C, 10%~90% (humidity)
<b>Certificate</b>	CE, FCC
<b>Environmental Protection</b>	Directive EU RoHS, WEEE, REACH

## Dimensions

---

