WIRELESS VIDEO TRANSMISSION

IP65 50m HD Wireless Video Link Pair





Key Features

- 5.8GHz
- IP65 rated
- 2 RF channels

Note: * In ideal conditions

- 10 -14VDC operation voltage
- High quality AHD 1080P (2MP) video
- 50 Metres HD range (Line of Sight)*
- 400 Metres CVBS range (Line of Sight)*
- 4 LED (RSSI) signal strength meter
- Directional antennas (Reduced interference)

The Genie RF50HD is a high-quality FHD compatible wireless video link designed for easy installation and reliable transmission. Housed in a compact IP65- rated weather resistant enclosure, both the transmitter and receiver are suitable for outdoor installations without the need for additional protection from the elements. Supporting up to 1080P resolution for AHD video

Supporting up to 1080P resolution for AHD video signals, our RF50HD can offer up to 50-metres of wireless range, and up to 400-metres in CVBS mode (line of sight).





Specification

Electrical

Operating Voltage	10—14V DC (Max)
Operating Current (Transmitter)	180mA (Max)
Operating Current (Receiver)	140mA (Max)

Transmitter

Operating Frequencies	5740MHz & 5860MHz
Transmit Power	<= 14dBm
Video Input	1Vpp
Video Modulation	FM

Receiver

Operating Frequencies	5740MHz & 5860MHz
RF Input Level	-85 ~ -10dBm
Video Output	0.6 ~ 0.9Vpp

Mechanical

Housing size without Aerial and Grommet	115 × 65 × 40mm
Housing Rating	IP65

Environmental

Temperature Range	-20 to + 55°C
Relative Humidity	95% (Non-Condensing)
Bandwidth (AHD 1080P)	40MHz
Bandwidth (CVBS)	5.5MHz
Distance (Line of sight)*	Up to 50 Metres FHD (2MP) Up to 400 Metres CVBS

Compliance

EN301-489

Accessories



RF2-4DP Dual Base Plate for use with RF200D, RF200V, RF450V, RF100HD and RF50HD (Maximum 1

video and 1 data)



RF200PM Pole Mount Kit for RF200D, RF200V, RF450V, RF100HD and RF50HD.

