

HDUBATXRX

ACTIVE BALUN

AHD, CVI, TVI and CVBS Active Video Balun



Key Features

- Supports HD-AHD, HD-TVI, HD-CVI, CVBS/analogue video transmission over UTP
- 720P/960P up to 800meters, 1080P/3MP/4MP/5MP up to 500meters
- 60dB cross talk and noise immunity
- Frequency response can be adjusted according to the specific circumstances
- Built-in anti-surge, anti-thunder and anti-inference functions
- DC12V/0.5-1A power adapter

The Genie HDUBATXRX is a single channel 5MP 4 in 1 HD analogue video UTP transmitter and receiver that transfers real-time HD analogue video signal up to 500m and 760P/960P (CVBS) up to 800meters through Cat5/5e/6 cable.



genie

Specification

Functions

Support	AHD/TVI/CVI/Analogue
Connector	Female BNC and terminal Block
Transmission distance	720P/960P: 800meters, 1080P/3MP/4MP/5MP: 500meters
CMRR	60dB
Impedance	BNC: 75 ohms, Terminal: 100 ohms

Others

Power adapter	DC12V/0.5-1A
Working Temperature	-10°C ~ 70°C
Storage Temperature	-30°C ~ 70°C
Humidity	0 ~ 95%
Dimensions	113 × 45.5 × 29 mm
Housing	Aluminium alloy
Category type	Cat5e/6 suggested

Application

